

## WHAT IS CLAIMED IS:

1. A bearing fixed assembly in a direct current fan, comprising:

5           a fan blade unit;  
          a fan base, being disposed next to the fan blade unit; and  
          a motor unit, being arranged between the fan blade unit;

10           wherein

          the fan blade unit, further comprises:

          an integral fan blade;  
          a spindle, being disposed at a lower periphery central position of the fan blade and extending to the fan base;

15           a motor casing, being disposed at a lower inner periphery side of the fan blade; and

          a magnet bar, being disposed at an inner side of the motor casing;

20           the fan base further comprises:

          a spindle seat, having a lower closed containing space filled with lubrication oil;

          a retaining ring, being attached to the spindle next to the spindle seat;

25           a washer, being arranged on top of the retaining ring; and

          at least a bearing, fitting with the spindle above the washer, and constituting a closed oil chamber with the spindle, the washer, the retaining ring, and the spindle seat; and

30

0591405-11401  
FOFFT "9046660

the motor unit surrounds the spindle seat and further comprises:

an insulation stand;

5 a plurality of silicon steel sheets,  
surrounding the insulation stand;

a circuit board, being disposed under the insulation stand; and

a plurality of coils, being wound in the insulation stand;

10 2. The bearing fixed assembly in a direct current fan  
as defined in claim 1, wherein the bearing is an oily bearing.

3. The bearing fixed assembly in a direct current fan  
as defined in claim 1, wherein the spindle seat has an annular  
15 recess with an inner ring and an outer ring to form a double  
layer structure and the fan blade unit is mounted within  
the inner ring with a stop ring in the annular recess.

20

25

30

00991406-111401